

Manual Reset Switch

Features

A push button operated switch which isolates the electrical supply to the valve in the event of power failure.

When power is subsequently restored to the valve, the push button must be depressed before the valve will open after which operation is as normal.

The Manual Reset Switch is remote mounted.

Installation

Remote Manual Reset Switch is suitable for screw fixing to a flat surface. Route electrical supply to valve through unit; electrical connections via screw terminals; cable entry 20mm diameter.

Specification

Product Code:	BC66ESB (Metal box) BC66ESB/P (Plastic box)
Remote model	BC66RSR (add voltage suffix)
Consumption:	1VA max.
Drop out time:	Typically 10ms
Protection:	IP65

Emergency Cut Out Switch

Features

A remote mounted push-to-break contacts/twist-to-reset contacts switch for emergency use. Available in metal or plastic wall mounting box.

Installation

Box is suitable for screw fixing to a flat surface.

Connect electrical supply through single pole switch block with screw terminals. Additional contact blocks for double pole and 3 phase applications available as accessories.

Specification

Contacts:	10A 500V max. Single pole (Extra contact blocks may be retro fitted)
Cable entry:	20mm
Temp. range:	-25°C to +70°C
Protection:	BC66ESB – IP65 Others – IP40

Dimensions, mm				
	Height	Width	Depth	Mount
BC66ESB	80	80	82	50x65
BC66ESB/P	85	66	94	49x54
BC66ESB/K	85	66	94*	54x67

Provengas Automatic Gas Proving System

Features

An automatic proving system for gas installations comprising a control panel and an isolating unit.

Connects into gas supply to safety shut off valve and proving cycle is manually initiated from control panel.

Has integral time switch for timed shut down and features key switch and emergency cut out switch for safety and security. Easy installation and commissioning, for use with any solenoid or electrohydraulic gas safety shut off valves.

Installation

The isolating unit may be either wall mounted or fixed directly to the gas valve. The control panel may be mounted in any convenient location in the same building as the isolating unit.

Specification

Product Code: PG001
Compatibility: 1st, 2nd & 3rd Family Gases
Electrical Supply: 230V 50Hz, 2A fused Gas Supply: 20mbar to 60mbar Ambient and Media Temp: 0°C to 55°C
See separate Literature ref CAT055/A or contact Watts Industries UK.

Other Products

Available From The Black Teknigas Range of Industrial And Combustion Controls:

Series 2000 Solenoid Valves
Teknigas Solenoid Valves
Thermocouples
Relay Valves
Gas Thermostats
Burners/Injectors
Pilots/Electrodes
High and Low Pressure Switches
Flow Controls
Level Controls
Gas Governors
Gas/Air Ratio Valves
Free Fall Fire Valves

